

The MMS Series Inverter/Charger



MMS1012-G – With GFCI outlet and 3 ft cord. Ideal for emergency vehicle applications.

MODEL NUMBERS

- MMS1012
- MMS1012-G

AVAILABLE FOR

- Emergency Vehicles
- Marine Systems
- RV Systems

AVAILABLE ACCESSORIES

- DC Load Disconnect
- Fuse Blocks
- MagWeb
- Remote - ME-ARC
- Remote - ME-RC
- Remote - MM-RC

The MMS Series Inverter / Charger is a pure sine wave inverter providing a cost effective solution for those with smaller power needs in mobile applications. Versatile, easy-to-use, and lightweight, the MMS Series provides a reliable base for your energy system.

Power Factor Corrected (PFC) Charger: Our PFC charger is built into all of our inverter/chargers. It uses less energy from a generator than a standard charger – using 25-30% less AC current than standard chargers.

Safe and reliable: The MMS Series is ETL Listed to the stringent requirements of UL/cUL 458 and CSA C22.2 #107.1-01 for mobile use.

Attractive styling: The modern, hourglass case, paired with the die cast aluminum base combines form with function, creating an attractive unit that uses its base as a heat sink for superior high temperature operation.

Features

Standard transfer relay:

The standard 20 amp transfer relay will pass AC power through the inverter when using shore or generator power.

Low/high battery protection:

If your battery voltage reaches below 10 VDC or above 17 VDC, the MMS Series will automatically shut down.

Versatile mounting:

Mount the MMS Series on a shelf, bulkhead, or even upside down.

Fan cooled:

The MMS Series is fan cooled, enabling the unit to work well in confined spaces. If the inverter does exceed its temperature limits, it will automatically shut down and then restart when it cools down.

Current overload protection:

The MMS Series will automatically shut down if its output wattage is exceeded or it detects a short in the wiring, saving the unit from costly damage.

Convenient switches:

The MMS Series comes with an on/off front-mounted switch with an easy-to-read LED indicator.

Circuit breaker protection:

This model comes with built in input and output circuit breakers for ease of installation.

Battery temp sensor:

The standard battery temp sensor monitors temperatures from 0 - 50° C.

Buy with ease:

The MMS Series is backed by a two-year (24-month) parts and labor warranty.



MMS Series Specifications

	MMS 1012	MMS 1012-G
Inverter Specifications		
Input battery voltage	9 to 17VDC	9 to 17VDC
Nominal AC output voltage	120 VAC ± 5%	120 VAC ± 5%
Output frequency and accuracy	60 Hz ± 0.1 Hz	60 Hz ± 0.1 Hz
Total Harmonic Distortion (THD)	< 5%	< 5%
1 msec surge current (amps AC)	38	38
100 msec surge current (amps AC)	21	21
5 sec surge power (real watts)	1750	1750
30 sec surge power (real watts)	1600	1600
5 min surge power (real watts)	1200	1200
30 min surge power (real watts)	1050	1050
Continuous power output at 25° C	1000 VA	1000 VA
Maximum continuous input current	133 ADC	133 ADC
Inverter efficiency (peak)	87%	87%
Transfer time	16 msec	16 msec
Search mode (typical)	5 watts	5 watts
No load (120VAC output, typical)	19 watts	19 watts
Waveform	Pure Sine Wave	Pure Sine Wave
Charger Specifications		
Continuous output at 25° C	50 ADC	50 ADC
Charger efficiency	84%	84%
Power factor	> 0.95	> 0.95
Input current at rated output (AC amps)	7	7
General Features and Capabilities		
Transfer relay capability	20 AAC (input current for charging and pass through)	
Battery temperature compensation	Yes, 15 ft BatteryTemp Sensor standard	
Internal cooling	0 to 59 cfm variable speed	
Overcurrent protection	Yes, with two overlapping circuits	
Overtemperature protection	Yes, on transformer and MOSFETS	
On/Off with status indicator	Yes, front mounted and easily accessible	
Low battery cutout	10VDC, adjustable with the ME-RC remote	
AC output	Hardwire	GFCI outlet
AC input	Hardwire	3 ft cord
Output circuit breaker	15 A	NA
Input circuit breaker	20 AAC	20 AAC
Listings	ETL Listed to UL/cUL458, CSA C22.2 #107.1-01, meets KKK-A-1822E standard	
Warranty	Two years	
Environmental Specifications		
Operating temperature	-20° C to +60° C (-4° F to 140° F)	
Nonoperating temperature	-40° C to +70° C (-40° F to 158° F)	
Operating humidity	0 to 95% RH non condensing	
Physical Specifications		
Dimensions (l x w x h)	16.6" x 8.4" x 4.7" (42 cm x 21 cm x 12 cm)	
Mounting	Shelf (top or bottom up) or bulkhead (vents up)	
Weight	23 lb (10.4 kg)	
Shipping weight	25 lb (11.3 kg)	
Max operating altitude	15,000' (4570 m)	
Construction	ABS plastic top and cast aluminum bottom	

